



SERVICE BULLETIN NO. 100

Section VIII, Division A
Service Bulletin 100
Issued April, 1965
Revise Oct. 1972

A Clinton SNORKEL Kit

for any application where

excessive dirt and

debris is encountered.

Here's what it will do for you -----

1. Increases life of engines
2. Insures maximum power from engines
3. Reduces costly repairs
4. Easy to clean
5. Easy to install
6. Keeps engines running cooler

PART NO. 70-57

**REPLACEMENT
ROPE FERRULE**

NOTE: Late 1972 production
will have replacement
ferrule as standard

Eliminates clogging of cooling fins and blower housing, resulting in overheating of engines.

Engine pulls in cleaner air away from operation.

Can be used on long life models 494, 498, and earlier models (1200, 1100, 900, 700) using Clinton Stamped Construction Recoil Starter.

Procedure For Attaching "Snorkel" Housing:

1. Pull over recoil starter until approx. 24" of rope is free.
2. Untie knot retaining handle & remove handle.
3. Thread rope through ferrule provided on "Snorkel" housing.
4. Replace starter handle.
5. Push "Snorkel" housing over blower housing until it bottoms on recoil starter.
6. Mark inner housing and drill 2 side holes (Size .190-.195, or #10 drill), also hole in center of housing (Size .250 or 1/4 in. drill).
7. Install the two Hex head slotted tapping screws in side holes and one Hex head washer tapping screw in center hole.

